



AUTO SCRUBBER DILUTION RATIO

8 ml NORTEC® CLEAN per 1 L Water

Cleaning Surface Area: 12.5 m² / l

Recommended cleaning: 3 times per week.

Use for regular maintenance.

1 SWEEP THE FLOOR

Sweep the floor to remove all loose soil and debris using a dust/dry mop. Pick up soil and debris with a broom and dust pan.

Note: It is best to sweep the floor with a dust/dry mop, as it holds grit and fine particles and takes them off the floor.

2 FILL AUTO SCRUBBING MACHINE WITH CLEANING SOLUTION

Fill the automatic scrubber with water and dilute NORTEC® CLEAN solution at a ratio of 1 oz / 1 gal (8 ml / 1 L).

3 MOVE MACHINE TO CLEANING AREA AND AFFIX PADS

Move the scrubbing machine to the area that needs cleaning. Plan the most appropriate scrub path for the floor. Affix pads to the scrubbing machine. Black or brown pads are suitable for cleaning densified power troweled finished floors. Red pads are recommended for polished surfaces.

4 TURN ON SOLUTION VALVE TO MAXIMUM FLOW

Turn on the solution valve to maximum flow. Allow water to commence dripping off the pads/brushes before lowering pad heads to floor (this will avoid causing donuts on the floor surface). Lower pads and turn on.

5 TURN ON VACUUM AND ADJUST WATER FLOW

Turn on vacuum, lower squeegee and begin scrub pattern. Adjust water flow when machine is moving to avoid flooding and splash.

6 DOUBLE SCRUB (IF NECESSARY)

When a double scrub is required, leave squeegee up and scrub floor without picking up solution on the first pass. Turn and scrub over the same path again with the squeegee lowered to pick up the soiled solution.

7 DISPOSAL OF SOILED SOLUTION

Dispose of the soiled solution according to your local government regulations.



MOP & BUCKET DILUTION RATIO

8 ml NORTEC® CLEAN per 1 L Water

Cleaning Surface Area: 250 - 300 m² / l

Recommended cleaning: 3 times per week.

Use for small or constricted areas, or to cleanup spills.

1 SWEEP FLOOR

Start cleaning in one corner and work the designated area.

For Heavily Soiled Areas: Sweep the floor with a concrete broom to help remove concrete fines caused by standard wear. Pick up the residue and dispose.

For Light/Normal Soiled Areas: Dust/dry mop* cleaning area. When finished sweeping, lift mop 0.5" to 1" (1.27 cm to 2.54 cm) off the floor and gently shake to remove any grit. Pick up loose soil with broom and dust pan and dispose.

*Dust/dry mop must be clean, as a dirty dust/dry mop grinds soil into the floor. Never use a treated dust mop.

2 WET MOP FLOOR

Dip wet mop* into bucket and wring out to damp. Cleaning solution should just barely drip from mop ends when mop is lifted out of the wringer.

*To avoid streaking, use only a rayon mop head.

3 MOP ONLY DEFINED AREA FOR CLEANING

Define area to be cleaned to eliminate over-mopping and partial cleaning. Use a standard figure eight motion. Flip over, wring, and rinse mop frequently. Change solution according to surface cleaning recommendation above.

4 DISPOSAL OF SOILED SOLUTION

Dispose of the soiled solution according to your local government regulations.

For more information or to order NORTEC® CLEAN please contact your local representative:

- Austria: + 43 7249 46 086
- Czech Republic: + 420 777 033 300
- Germany: +49 34207 40 80 0
- Poland: +48 32 250 34 27
- Switzerland: +41 79 657 17 55



Scan QR code for more product information



POULTICE DILUTION RATIO

32 ml NORTEC® CLEAN per 1 L Water

Cleaning Surface Area: Spot treatment

Recommended cleaning: As needed

Use for spot removal of significant oil or grease staining. This is not a regular maintenance procedure. Several applications of NORTEC® CLEAN may be needed to remove severe stains from concrete surfaces.

1 SELECT SMALL AREA TO BE TREATED

Select area(s) to be poulticed. Remember, although grease and oil may occur all over the floor area, you are best to treat small areas that can be controlled easily.

2 SWEEP THE FLOOR

Remove all loose soil and fine grit using a dust/dry mop. Pick up soil and debris with a broom and dust pan.

3 MOP DOWN AREA WITH SOLUTION

Use NORTEC® CLEAN diluted at 4 oz / 1 gal (30 ml / L) and agitate solution with the mop to assist the product in better penetrating the soiled surface.

*Use a rayon mop head to avoid streaking.

4 COVER AND ALLOW SOLUTION TO PENETRATE

Cover the wet surface with plastic film and tape down the edges. Allow area to remain wet for 10 - 15 minutes or longer if possible. Do not allow to dry on surface.

5 UNCOVER AND REMOVE SOLUTION

Remove plastic film and pick up soiled solution with a wet/dry vacuum.

6 EXAMINE THE SURFACE

Examine the surface for any signs of grease or oil. A white cloth rubbed on the surface will show a black or dark color if surface oil or grease is present. If soil still remains, repeat steps 3 - 6.

7 DISPOSAL OF SOILED SOLUTION

Dispose of the soiled solution according to your local government regulations.

Emergency Telephone Number: +49 (0) 700-2411-2112 (CAL)
For Commercial Use Only.